

**date** 12/19/2023 **page** 1 of 3

# MODEL: CPI-1375-88T | DESCRIPTION: PIEZO BUZZER INDICATOR

#### **FEATURES**

- piezo
- 88 dB @ 0.1 m
- through hole






## **SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated voltage			12		Vdc
operating voltage		4.0		16.0	Vdc
current consumption	at rated voltage			15	mA
rated frequency		3,600		4,600	Hz
sound pressure level	at 10 cm, rated voltage	88			dB
tone	continuous				
dimensions	Ø13.9 x 7.5				mm
weight				1.1	g
material	PBT (black)				
terminal	pins (gold plating)				
operating temperature		-40		85	°C
storage temperature		-40		90	°C
washable	yes				
RoHS	yes				


Notes: 1. All specifications measured at 5~35°C, humidity at 45~85%, under 86~106 kPa pressure, unless otherwise noted.

## **SOLDERABILITY**

parameter	conditions/description	min	typ	max	units
hand soldering	for maximum 2 seconds	330		380	°C
wave soldering	see recommended wave soldering profile			250	°C




## **MECHANICAL DRAWING**




2-ø0<u>.9</u> Hole

Recommended PCB Layout Top View

## **PERFORMANCE CURVES**





Voltage vs. Current Consumption

Additional Resources: Product Page

CUI DEVICES | MODEL: CPI-1375-88T | DESCRIPTION: PIEZO BUZZER INDICATOR

**date** 12/19/2023 | **page** 3 of 3

#### **REVISION HISTORY**

rev.	description	date	
1.0	initial release	12/19/2023	

The revision history provided is for informational purposes only and is believed to be accurate.



CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.