

date 07/27/2023

page 1 of 3

SERIES: SJ1-4251X | DESCRIPTION: AUDIO JACK


FEATURES

- · low profile design
- switch options include:
- no switch
- tip switch
- ring switch
- tip and ring switch





PART NUMBER KEY



SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated input voltage			12		Vdc
rated input current				1	А
contact resistance	between terminal and mating plug between terminal in a closed circuit			50 30	$m\Omega$
insulation resistance	at 500 Vdc	100			МΩ
voltage withstand	at 50/60Hz for 1 minute			500	Vac
insertion/withdrawal force		0.3		3	kg
operating temperature		-25		85	°C
life			5,000		cycles
flammability rating	UL94V-O				
RoHS	yes				

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
wave soldering	dipped in solder pot for 5 ±0.5 seconds	255	260	265	°C

PLATING/COLOR

gold flash

gold flash

gold flash

gold flash

gold flash


gold flash


black


-0.8×1.5


MECHANICAL DRAWING


units: mm tolerance: X.X ±0.2 mm X.XX ±0.10 mm X.XXX ±0.050 mm unless otherwise specified














DESCRIPTION

terminal 1

terminal 2

terminal 3

terminal 4

terminal 5

terminal 6

MATERIAL

t=0.25

t=0.20

t=0.20

t=0.25

t=0.20

phosphorous bronze


phosphorous bronze


phosphorous bronze

phosphorous bronze

phosphorous bronze

phosphorous bronze





Model No.	SJ1-42514	SJ1-42515TS	SJ1-42516
Schematic	01 04 03	0 1 0 4 0 3 0 5 0 5	01 04 03 06 05 05
PIN			
1	sleeve	sleeve	sleeve
2	tip	tip	tip
3	ring 1	ring 1	ring 1
4	ring 2	ring 2	ring 2
5	NP	tip switch	tip switch
6	NP	NP	ring switch

REVISION HISTORY

rev.	description	date	
1.0	initial release	10/27/2005	
1.01	new template applied	12/15/2011	
1.02	brand update	01/31/2020	
1.03	discontinued model SJ1-42515RS; logo, datasheet style update	08/18/2022	
1.04	product reengineered for improved manufacturability and production yield, see PCN for details	07/27/2023	

The revision history provided is for informational purposes only and is believed to be accurate.



CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.