

MODEL: SJ3-35074A | DESCRIPTION: AUDIO JACK

FEATURES

- 3.5 mm audio jack
- through hole
- tray packaging



.....

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated input voltage			12		Vdc
rated input current				1	А
contact resistance				30	mΩ
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	for 1 minute			500	Vac
insertion/withdrawal force		0.3		3	kg
operating temperature		-25		85	°C
life			5,000		cycles
flammability rating	UL94V-0				
RoHS	yes				


SOLDERABILITY


.....


parameter	conditions/description	min	typ	max	units
wave soldering	for max 5 seconds	255	260	265	°C
	260°C 180°C 120°C 20°C A. Preheating B. Soldering C. Cooling		-		

MECHANICAL DRAWING











ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
1	housing	PBT (UL94V-0)	black
2	terminal 1	copper alloy t=0.25	silver over nickel
3	terminal 2	copper alloy t=0.25	silver over nickel
4	terminal 3	copper alloy t=0.40	silver over nickel
5	terminal 4	copper alloy t=0.25	silver over nickel






Recommended PCB Layout Top View

.....

Model No.	SJ3-35074A	
Schematic	0 1 0 4 0 3 0 2	
PIN		
1	sleeve	
2	ring 2	
3	tip	
4	ring 1	



.....

cuidevices.com

REVISION HISTORY

rev.	description	date	
1.0	initial release	06/12/2024	

The revision history provided is for informational purposes only and is believed to be accurate.

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.



CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.